

1U Type Industrial Power Supply

EFAP-461

EPS1U

- 460 watts Output Power**
- Dual +12V Output Rails**
- EPS1U Application**
- Meet 1U Rack Mount System**



Dimensions: 106(W) x 40(H) x 300(D) mm

Features:

- ⦿ Universal Power Input
- ⦿ Active Power Factor Correction
- ⦿ Dual +12V Output Rails
- ⦿ Dual Processors Application
- ⦿ Remote DC Sense on +5V and +3.3V
- ⦿ Short Circuit Protection
- ⦿ Over Current Protection
- ⦿ Over Voltage Protection
- ⦿ Over Power Protection
- ⦿ MTBF >100,000 Hours

General Specifications:

- ⦿ Input Range: 100 to 240 VAC, +/-10%
- ⦿ Power Factor: 0.95 minimum
- ⦿ Efficiency: 70% minimum, at full load
- ⦿ Hold up Time: 20mS minimum, at full load
- ⦿ PSON (Remote ON/OFF): TTL compatible signal
- ⦿ Power Good: 100 to 500 ms, TTL compatible signal
- ⦿ Cooling Fan: 40x40x28 mm (SANYO)
- ⦿ Operating Temperature: 0 to 50 degree
- ⦿ Operating Humidity: 20 to 90 %

Agency Requirements:

- ⦿ Harmonic: Meet EN61000-3-2 standards
- ⦿ EMI/RFI: CE, FCC class B and CISPR class B
- ⦿ Safety: UL, cUL, CB, TUV

Electrical Specifications:

Regulation, Ripple & Noise:

Output	+5V	+3.3V	+12V	-5V	-12V	5Vsb
Load Regulation	± 5%	± 5%	± 5%	± 5%	± 5%	± 5%
Cross Regulation	± 5%	± 5%	± 5%	± 5%	± 5%	± 5%
Line Regulation	± 1%	± 1%	± 1%	± 1%	± 1%	± 1%
Ripple & Noise	50mV	50mV	120mV	100mV	120mV	50mV

Input and Output Ratings:


Input			Output								
Voltage	Frequency	Current	Watt	Load	+5V	+3.3V	+12V1	+12V2	-5V	-12V	5Vsb
90 – 264 VAC	47-63 Hz	8A max	460W	Max Load	30A	30A	18A	18A	1A	1A	2A
				Min Load	1A	0A	1A	1A	0A	0A	0A

- Note:
1. The +12V1 & +12V2 combine output currents maximum are 30A
 2. The +5 & +3.3 Volt combine total output shall not exceed 220W
 3. The +5, +3.3 and +12 Volt combine total output shall not exceed 433W
 4. Noise bandwidth is from DC to 20 MHz.

1U Type Industrial Power Supply

EFAP-461

Dimensions (Unit: mm):



Rev: 1.2 May. 29, 03